

TECHNICAL DATA

2626-S | Spare Sensor, standard-accuracy



Product overview: 2626-S | Spare Sensor, standard-accuracy

One of the potential advantages of a digital thermo-hygrometer is that instead of sending the entire unit out for calibration, you can simply swap sensors and send only the sensors due for calibration out of the lab. The 1620A "DewK" Thermo-Hygrometer allows you to swap sensors without shutting it down or discontinuing your other readings.

Smart sensors make this possible because all of the calibration information is contained inside the sensor. Your costs are reduced because the 1620A never needs to be calibrated since it is only a display. Spare sensors like the 2626-S are less expensive to store, ship and recalibrate than an extra chart recorder.

The 2626-S is a spare standard-accuracy smart sensor for all models of the "DewK" Thermo-Hygrometer.

Specifications: 2626-S | Spare Sensor, standard-accuracy

Size (L x Dia): 79 mm x 19 mm (3.1 x 0.75 in)

Ordering information



2626-S

Spare Sensor, standard-accuracy

Fluke. *Keeping your world up and running.®*

Fluke Europe B.V.

P.O. Box 1186
5602 BD Eindhoven
The Netherlands
www.fluke.com/en

©2026 Fluke Corporation. All rights reserved.
Data subject to alteration without notice.
03/2026

For more information call:

In Middle East/Africa
+31 (0)40 267 5100

**Modification of this document is not permitted
without written permission from Fluke
Corporation.**